

[Help](#)

```

extern "C" {
#include "temperedstable1d_std.h"
#include "enums.h"
}
#include "math/levy_fd.h"
extern "C" {
#if defined(PremiaCurrentVersion) && PremiaCurrentVersion < (2007+2) //The "#els
    static int CHK_OPT(FD_ImpExp)(void *Opt, void *Mod)
    {
        return NONACTIVE;
    }
    int CALC(FD_ImpExp)(void *Opt, void *Mod, PricingMethod *Met)
    {
        return AVAILABLE_IN_FULL_PREMIA;
    }
#else
    static int ImpExp(int am, double S0, NumFunc_1 *p, double T, double r, double

        double price0, delta0;
        int flag_callput, flag_stdbarrier;
        double rebate = 0.;

        /*Construction of the model*/
        TS_measure measure(alphap, alphas, lambdap, lambdam, cp, cm, dx);

        double K = p->Par[0].Val.V_DOUBLE;
        double k = 3;
        double A1 = log(2. / 3) + T * measure.espX1 - k * sqrt(T * measure.varX1);
        double Ar = log(2.) + r * T + k * sqrt(T * measure.varX1);
        if (A1 < -30) A1 = -30;
        if (Ar > 30) Ar = 30;
        int N1 = (int)ceil(-A1 / dx);
        int Nr = (int)ceil(Ar / dx);
        int N = N1 + Nr;
        A1 = -N1 * dx;
        Ar = Nr * dx;

```

```

    if ((p->Compute) == &Put)
        flag_callput = 2;
    else /*if ((p->Compute)==&Call)*/
        flag_callput = 1;

    flag_stdbarrier = 1;

    /*Price Computation*/
    if (flag_scheme == 1)
        vector<double> u = price2(am, measure, flag_callput, flag_stdbarrier, r, d
    else
        vector<double> u = price2c(am, measure, flag_callput, flag_stdbarrier, r,

    /*Price */
    *ptprice = price0;

    /*Delta */
    *ptdelta = delta0;

    return OK;
}

int CALC(FD_ImpExp)(void *Opt, void *Mod, PricingMethod *Met)
{
    TYPEOPT *ptOpt = (TYPEOPT *)Opt;
    TYPEMOD *ptMod = (TYPEMOD *)Mod;
    double r, divid;

    r = log(1. + ptMod->R.Val.V_DOUBLE / 100.);
    divid = log(1. + ptMod->Divid.Val.V_DOUBLE / 100.);
    return ImpExp(ptOpt->EuOrAm.Val.V_BOOL, ptMod->S0.Val.V_PDDOUBLE,
        ptOpt->PayOff.Val.V_NUMFUNC_1, ptOpt->Maturity.Val.V_DATE - pt
}

static int CHK_OPT(FD_ImpExp)(void *Opt, void *Mod)
{
    if ((strcmp(((Option *)Opt)->Name, "CallEuro") == 0) || (strcmp(((Option *)O

        return OK;
}

```

```

    return WRONG;
}
#endif //PremiaCurrentVersion

static int MET(Init)(PricingMethod *Met, Option *Opt)
{
    static int first = 1;

    if (first)
    {
        Met->HelpFilenameHint = "FD_ImpExp_ts";
        Met->Par[0].Val.V_PDOUBLE = 0.001;
        Met->Par[1].Val.V_INT2 = 400;
        Met->Par[2].Val.V_ENUM.value = 1;
        Met->Par[2].Val.V_ENUM.members = &PremiaEnumExpPart;
        first = 0;
    }

    return OK;
}

PricingMethod MET(FD_ImpExp) =
{
    "FD_ImpExp",
    { {"Space Discretization Step", DOUBLE, {500}, ALLOW}, {"TimeStepNumber", IN
        {"Explicit Part", ENUM, {100}, ALLOW},
        {" ", PREMIA_NULLTYPE, {0}, FORBID}
    },
    CALC(FD_ImpExp),
    {"Price", DOUBLE, {100}, FORBID}, {"Delta", DOUBLE, {100}, FORBID}, {" ", P
    CHK_OPT(FD_ImpExp),
    CHK_split,
    MET(Init),
    0,
    "fd_impexp_ts"
};
}

```