

[Help](#)

```
#include <stdlib.h>
#include "cir1d_std.h"

/*Product*/
static double dt, dr, r_min, r_max;
static double *r_vect, *disc, * *Ps;
static double *pu, *pm, *pd;
static long Ns; /* ,Nt0; */

/* static int j_max;*/

/*Memory Allocation*/
static void memory_allocation(long Nt)
{
    int i;

    if ((r_vect = malloc(sizeof(double) * (Ns + 1))) == NULL)
    {
        printf("Allocation error");
        exit(1);
    }
    if ((disc = malloc(sizeof(double) * (Ns + 1))) == NULL)
    {
        printf("Allocation error");
        exit(1);
    }
    if ((pu = malloc(sizeof(double) * (Ns + 1))) == NULL)
    {
        printf("Allocation error");
        exit(1);
    }
    if ((pm = malloc(sizeof(double) * (Ns + 1))) == NULL)
    {
        printf("Allocation error");
        exit(1);
    }
    if ((pd = malloc(sizeof(double) * (Ns + 1))) == NULL)
    {
        printf("Allocation error");
```

```
        exit(1);
    }
    if ((Ps = malloc(sizeof(double *) * (Nt + 1))) == NULL)
    {
        printf("Allocation error");
        exit(1);
    }
    for (i = 0; i <= Nt; i++)
    {
        Ps[i] = malloc(sizeof(double) * (Ns + 1));
    }

    return;
}

/*Memory Desallocation*/
static void free_memory(long Nt)
{
    int i;

    free(r_vect);
    free(pu);
    free(pm);
    free(pd);
    free(disc);

    for (i = 0; i < Nt + 1; i++)
        free(Ps[i]);
    free(Ps);

    return;
}

/*Computation of probabilities*/
static int init_prob(double k, double sigma, double theta, double T, double t0,
{
    double df;
    int j;
    double beta, alpha1, alpha2;
```

```

dt = (T - t0) / (double)Nt;
dr = sigma * sqrt(3. / 4.*dt);
alpha1 = (4.*k * theta - SQR(sigma)) / 8.;
alpha2 = k / 2.;
beta = dr / (2.*dt);
r_min = (-beta + sqrt(SQR(beta) + 4.*alpha1 * alpha2)) / (2.*alpha2);
r_max = (beta + sqrt(SQR(beta) + 4.*alpha1 * alpha2)) / (2.*alpha2);

Ns = (int)ceil((r_max - r_min) / dr);

memory_allocation(Nt);
for (j = 0; j <= Ns; j++)
{
    r_vect[j] = r_min + (double)j * dr;
    disc[j] = exp(-SQR(r_vect[j]) * dt);
    df = ((4.*k * theta - SQR(sigma)) / (8.*r_vect[j]) - r_vect[j] * k / 2.) *

    if (j == 0)
    {
        pu[j] = 1. / 6. + (SQR(df) - df) / 2.;
        pm[j] = df - 2.*pu[j];
        pd[j] = 1. - pu[j] - pm[j];
    }
    else if (j == Ns)
    {
        pd[j] = 1. / 6. + (SQR(df) + df) / 2.;
        pm[j] = -df - 2.*pd[j];
        pu[j] = 1. - pd[j] - pm[j];
    }
    else
    {
        pu[j] = 1. / 6. + (SQR(df) + df) / 2.;
        pd[j] = pu[j] - df;
        pm[j] = 1. - pu[j] - pd[j];
    }
}

return OK;
}

```

```

/*Zero Coupon Bond*/
static int zcb_cir(long Nt)
{
    int i, j;

    /*Maturity conditions for pure discount Bond*/
    for (j = 0; j <= Ns; j++)
        Ps[Nt][j] = 1.;

    /*Dynamic Programming*/
    for (i = Nt - 1; i >= 0; i--)
        for (j = 0; j <= Ns; j++)
        {
            if (j == 0)
                Ps[i][j] = disc[j] * (pu[j] * Ps[i + 1][j + 2] + pm[j] * Ps[i + 1][j + 1] + pd[j] * Ps[i + 1][j]);
            else if (j == Ns)
                Ps[i][j] = disc[j] * (pd[j] * Ps[i + 1][j - 2] + pm[j] * Ps[i + 1][j - 1] + pu[j] * Ps[i + 1][j]);
            else
                Ps[i][j] = disc[j] * (pu[j] * Ps[i + 1][j + 1] + pm[j] * Ps[i + 1][j] + pd[j] * Ps[i + 1][j - 1]);
        }
    return 1.;
}

static int bond_cir1d(double r0, double k, double t0, double sigma, double theta)
{
    int j;
    double val, val1;

    /*Compute probabilities*/
    init_prob(k, sigma, theta, T, t0, Nt);

    /*Compute Zero Coupon Prices*/
    zcb_cir(Nt);

    /*Linear Interpolation*/
    j = 0;
    while (r_vect[j] < r0)
        j++;
    val = Ps[0][j];
    val1 = Ps[0][j - 1];

```

```

/*Price*/
*price = val + (val - val1) * (r0 - SQR(r_vect[j])) / (SQR(r_vect[j]) - SQR(r_

/*Memory Disallocation*/
free_memory(Nt);

return OK;
}

int CALC(FD_ZCBOND)(void *Opt, void *Mod, PricingMethod *Met)
{
    TYPEOPT *ptOpt = (TYPEOPT *)Opt;
    TYPEMOD *ptMod = (TYPEMOD *)Mod;

    return bond_cir1d(ptMod->r0.Val.V_PDOUBLE, ptMod->k.Val.V_DOUBLE, ptMod->T.Val
        ptMod->theta.Val.V_PDOUBLE, ptOpt->BMaturity.Val.V_DATE, Met
}

static int CHK_OPT(FD_ZCBond)(void *Opt, void *Mod)
{
    if ((strcmp(((Option *)Opt)->Name, "ZeroCouponBond") == 0))
        return OK;
    else
        return WRONG;
}

static int MET(Init)(PricingMethod *Met, Option *Opt)
{
    if (Met->init == 0)
    {
        Met->init = 1;

        Met->Par[0].Val.V_LONG = 400;

    }
}

```

```
    return OK;
}

PricingMethod MET(FD_ZCBond) =
{
    "FD_Explicit_Cir1d_ZCBond",
    { {"TimeStepNumber", LONG, {100}, ALLOW},
      {" ", PREMIA_NULLTYPE, {0}, FORBID}
    },
    CALC(FD_ZCBOND),
    {{"Price", DOUBLE, {100}, FORBID}, {" ", PREMIA_NULLTYPE, {0}, FORBID}},
    CHK_OPT(FD_ZCBond),
    CHK_ok,
    MET(Init)
} ;
```