

[Help](#)

```
#include "callable.h"

static TYPEOPT NoCall =
{
    {"Strike", PDOUBLE, {0}, ALLOW, SETABLE},
    {"Maturity (in days)", INT, {0}, ALLOW, SETABLE},
    {"Nominal Coupon Rate", PDOUBLE, {0}, ALLOW, SETABLE},
    {"Nominal Recovery", PDOUBLE, {0}, ALLOW, SETABLE},
    {"PutStrike", PDOUBLE, {0}, ALLOW, SETABLE},
    {"Calltrike", PDOUBLE, {0}, ALLOW, SETABLE},
    {"LowerBarrier", PDOUBLE, {0}, IRRELEVANT, UNSETABLE},
    {"UpperBarrier", PDOUBLE, {0}, IRRELEVANT, UNSETABLE},
    {"Window (in days)", INT, {0}, IRRELEVANT, UNSETABLE},
    {"Period (in days)", INT, {0}, IRRELEVANT, UNSETABLE},
};

static int OPT(Init)(Option *opt, Model *mod)
{
    TYPEOPT *pt = (TYPEOPT *) (opt->TypeOpt);

    if (opt->init == 0)
    {
        opt->init = 1;
        opt->nvar = 10;
        opt->nvar_setable = 6;

        pt->Strike.Val.V_PDOUBLE = 100.;
        pt->Maturity.Val.V_INT = 125;
        pt->Coupon.Val.V_PDOUBLE = 0.;
        pt->Recovery.Val.V_PDOUBLE = 0.;
        pt->PutStrike.Val.V_PDOUBLE = 0.;
        pt->CallStrike.Val.V_PDOUBLE = 103.;
        pt->LowerBarrier.Val.V_PDOUBLE = 0.;
        pt->UpperBarrier.Val.V_PDOUBLE = 0.;
        pt->Window.Val.V_INT = 0;
        pt->Period.Val.V_INT = 0;
    }

    return OK;
}
```

}

MAKEOPT(NoCall);